

Product Information Bulletin

GREENGUARD Certification Program - Insulspan SIP System

(Two pages attached)



As part of our commitment to quality and ongoing sustainability initiatives, Insulspan® maintains GREENGUARD Certification for the Insulspan SIP (Structural Insulating Panel) System. The Insulspan SIP System is an energy efficient building system consisting of a PlastiSpan® or EnerSpan® insulation core with oriented strand board (OSB) structurally laminated to the interior and exterior faces.

GREENGUARD certification is provided by UL Environment, an independent global safety science organization using their processes and procedures in accordance with established environment and safety standards.

The GREENGUARD Certification mark on the Insulspan SIP System gives assurance that products designed for use in indoor spaces meet strict chemical emissions limits, which contribute to the creation of healthier interiors. Achieving GREENGUARD Certification gives credence to Plasti-Fab sustainability claims, backing them with empirical scientific data from an unbiased, third-party organization.

The GREENGUARD standard achieved by the Insulspan SIP System includes health based criteria for additional chemicals and also requires lower total VOC emissions levels to ensure that products are acceptable for use in environments such as schools and healthcare facilities.

The attached GREENGUARD Gold Certificate of Compliance from UL Environment provides additional information regarding certification criteria used to establish the listing for the Insulspan SIP System.

GREENGUARD certified product listings can be found at: https://spot.ul.com/main-app/products/detail/5ad1ebc855b0e82d946a7171?page_type=Products%20Catalog

GREENGUARD Gold Certification Criteria for Building Products and Interior Finishes

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC ^(A)	-	0.22	mg/m ³
Formaldehyde	50-00-0	9 (7.3 ppb)	µg/m ³
Total Aldehydes ^(B)	-	0.043	ppm
4-Phenylcyclohexene	4994-16-5	6.5	µg/m ³
Particle Matter less than 10 µm ^(C)	-	20	µg/m ³
1-Methyl-2-pyrrolidinone ^(D)	872-50-4	160	µg/m ³
Individual VOCs ^(E)	-	1/2 CREL or 1/100th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C₆ – C₁₆ range, with responses calibrated to a toluene surrogate. Maximum allowable predicted TVOC concentrations for GREENGUARD Gold (0.22 mg/m³) fall in the range of 0.5 mg/m³ or less, as specified in CDPH Standard Method V1.2.

(B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

(C) Particle emission requirement only applicable to HVAC Duct Products with exposed surface area in air streams (a forced air test with specific test method) and for wood finishing (sanding) systems.

(D) Based on the CA Prop 65 Maximum Allowable Dose Level for inhalation of 3,200 g/day and an inhalation rate of 20 m³/day

(E) Allowable levels for chemicals not listed are derived from the lower of 1/2 the California Office of Environmental Health Hazard Assessment (OEHHA) Chronic Reference Exposure Level (CREL) as required per the CDPH/EHLB/Standard Method v1.2 and BIFMA level credit 7.6.2 and 1/100th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).

